

# MIL-STD-1553B

## ASP55 Remote Terminal RT ASIC 1553B

The ASP55 is a cost effective MIL-STD-1553B Remote Terminal ASIC sub-system developed in a radiation tolerant technology qualified for Space applications.

The ASP55 is able to manage the MIL-STD-1553B dialogue in remote terminal mode only and has a dual bus capability.

This product shall be used in addition with the ASP54D MIL-STD-1553B Dual Transceiver or two MIL-STD-1553B Single Transceivers in order to manage dual redundant MIL-STD-1553B applications.

It can be connected, on one hand, to a dual redundant MIL-STD-1553B bus with an external isolation transformer

for each bus and, on the other hand, to the user thanks to an interface composed of a 16-bit data bus, a 12-bit address bus and a control bus. Sub-system easy integration is achieved thanks to the opened user interface and optimised architecture. It is possible to connect the ASP55 to register or memory components without additional processing unit. Dedicated services are also provided in order to download the user application from protocol management tasks: words validity is automatically checked and only valid messages are transmitted to the application. The ASP55 low power consumption and radiation tolerance, better than 100 kRads (functional), are especially relevant for Space applications.

### Key Features

- Dual MIL-STD-1553B bus capability
- Fully compliant to MIL-STD-1553B standard
- 0,5  $\mu$ m CMOS Radiation Tolerant technology
- Remote Terminal designed for Space applications requiring radiation tolerant components
- Remote Terminal validated according to Validation Test Plan SAE AS 4111
- Pin-to-pin compatible with Airbus DS former Remote Terminal ASIC ASP20
- Flat-pack package

### Main application fields

- Any equipment designed for severe environment, requiring radiation tolerant components

### Budgets

- Packaging MQFP 84 pins
- Size 30 x 30 mm<sup>2</sup>
- Mass 9 g
- Power 250 mW max


### Interfaces

- Voltage in Full 5 V
- Sub-system Bus Address/Data
- Bus 1553 dual transceiver (eg ADT822)
- Clock 10 MHz
- 1553 Address 6 pins (including 1 for parity)

### Environments / Reliability

- Temperature -55 °C to +125 °C
- Radiation 100 krad total dose  
SEU < 10-4 per day  
(LET < 30 MeV)  
Latchup free  
(LET level > 80 MeV)
- Failure occurrence < 50 fit @ 50 °C

## Main functions



- Words validity check
- Transmission of only valid messages to the application
- Management of the status word and of the BIT word
- Programmable no response time out period
- Inhibition of driver externally provided
- Management of the user interface
- Management of a configuration PROM which characterises the terminal for each sub-address:
  - Legality / illegalit
  - Word count associated
  - Selection of indirect addressing
  - Flip / flop buffering
  - User type (register, CAN, memory)

## Technical features

Gate array technologie (12000 gates)  
 Operating frequency  
 Supply voltage  
 power consumption  
 Temperature range  
 Radiation tolerance

MG2RT 0.5  $\mu$ m From ATMEL  
 10 MHz  
 5 V  $\pm$  10%  
 250 mW max.  
 -55  $^{\circ}$ C to +125  $^{\circ}$ C  
 • 30 kRads (parametric)  
 • 100 kRads (functional)  
 • latch-up immune  
 • 84 pins Flat Pack  
 • 30x30mn MQFP  
 9 g

Packaging

Mass